



Technical Data Sheet

Product Name:	RENU 2010 Primer-Sealer
Size:	available in 18.9L and 3.78L sizes
Description:	Interior acrylic primer-sealer for new or acrylic painted surfaces. Can be used on most interior surfaces.
Type:	Acrylic
Colour:	Pale Grey
Viscosity:	95-100 KU
Coverage:	10 m ² /litre
Drying Time:	Touch – 30-60 min. Recoat after minimum 4 hours,
Concentration of Solids:	Per weight: 40-60%
VOC:	43 g/L (average)

Surface Preparation: Ensure all surfaces are free of contaminants, mildew, or peeled paint. Glossy surfaces must be sanded to ensure the adhesion of primer or new paint. For best results, wash surfaces with TSP (Trisodium phosphate). Rinse and allow sufficient drying time.

New Gypsum: Surface must be clean and dry. Make sure all dust has been removed after sanding.

Interior New Wood: Use of RENU 2010 is not recommended for this use. Use of an anti-bleeding primer for certain types of wood (eg. Pine, spruce, and cedar) is recommended.

New Concrete or Cement: New concrete must be dry before being painted. It must dry at least one month per inch of thickness. Wash with muriatic acid and rinse thoroughly. Apply one coat of RENU 2010 as is.

Latex Painted Surfaces: Apply one coat.

Alkyd Painted Surfaces: Sand then wash for an optimized adherence. Do not use this primer on the floor.

Application: Thoroughly shake the can and then use a stir stick to mix the content all the way to the bottom of the can. Use a synthetic paintbrush (nylon or polyester) or a 13 mm anti-lint roller. The primer can be diluted with water up to 10 % in order to use a sprayer and get an even spread. Temperature must be between 10°C and not over 32°C. The humidity level must be lower than 50% and the room must be well ventilated. Apply one coat. Allow proper drying time before applying paint.



RENU 2010 PRIMER-SEALER

- Cleaning Tools:** Wash all tools with soap and water.
- Storage:** Store in a dry and well-ventilated area. Temperature should be around 20°C. **Keep from freezing.**
- Disposal:** RENU Primer-Sealer can be recycled. Consult with your municipality in order to dispose of used paint properly.

Keep out of reach of children.