



Technical Data Sheet

Product Name:	RENU Interior Latex. The information on this sheet is valid for all RENU Interior Latex colours
Size:	available in 18.9L and 3.78L sizes
Description:	High quality low sheen paint that can be used on most interior surfaces.
Type:	Acrylic
Gloss level:	Velvet 2-8 (60°)
Colours:	Available in a range of colours. Can be tinted with other RENU colours. Colour may vary slightly from batch to batch.
Viscosity:	95-100 K U
Coverage:	12 m ² /litre
Drying Time:	Touch – 30-60 min. - 2 nd coat – 6-9 hours
Concentration of Solids:	Per weight: 40-60%
VOC:	43 g/L (average)
Surface Preparation:	<p>Ensure all surfaces are free of contaminants, mildew, or peeled paint Glossy surfaces must be sanded to ensure the adhesion of primer or new paint. For best results, wash surfaces with TSP (Trisodium phosphate). Rinse and allow sufficient drying time.</p> <p><u>New Gypsum:</u> Surface must be clean and dry. Use of a latex primer such as RENU 2010 is recommended. <u>Interior Raw Wood:</u> Use of an anti-bleeding primer for certain types of wood (eg. Pine, spruce, and cedar) is recommended <u>Latex Painted Surfaces:</u> If needed, a latex primer such as RENU 2010 can be used. <u>Alkyd Painted Surfaces:</u> Use of a primer made for this type of transition is recommended.</p>
Application:	<p>Do not apply in high humidity or during excessive heat. Do not apply product below 10°C or above 32°C. Apply in a well-ventilated room. For best results, apply 2 coats of paint. Allow enough dry time between coats. Drying time will vary depending on temperature, humidity, ventilation and the thickness of the coats.</p> <p>Shake well and use a stirring stick in order to get all product mixed. A synthetic paintbrush (nylon or polyester) or a 13mm anti-lint roller is recommended for best results.</p>



RENU 2XXX Interior Acrylic Latex

For a spray application, the paint can be diluted 10-15% with water for a more even application.

Cleaning Tools:

Wash all tools with soap and water immediately after use.

Storage:

Store in a dry and well-ventilated area. Temperature should be around 20°C. **Keep from freezing.**

Disposal:

RENU paint can be recycled. Consult with your municipality in order to dispose of used paint properly.

Maintenance:

To maximize the durability of new paint, wait 4 weeks before washing the surface. To wash surface, use a soft cloth or sponge and a mild household soap. Do not use abrasive or harsh cleansers. Rinse soap residue.

Keep out of reach of children.